WERMA®

WERMA®

CST55

- Industrial design, matching modern machines
- 360° visible, all-round clear light
- 2-4 layers and buzzer are optional, flexible and suitable for more needs
- 85 decibel pulse to clearly identify the signal
- Complete kit (including mounting brackets and cables) for quick and easy installation

CE IP40 +50°C +122°F -20°C -4°F PC PC+ABS/ASA 85 dB

RST 56

- Additional transparent housing: strengthened safety, extends its duration
- Dual mounting options: base /tube/ foldable/ installation
- IP66/IP69k: ideal for industrial environments
- Adjustable buzzer max90db, dial code to adjust
- 2-5 tiers plus buzzer as option match majority application

CE IP66/IP69K +50°C +122°F -30°C -22°F PC PC/ASB Max 90dB

MST71

- Excellent visibility through convex lens from all the positions and directions.
- High flexibility with 8 tones to select and up to 102dB sound output
- Two tones setting directly enables working status easy to distinguish
- Simple and intuitive installation with POKA YOKE
- Pre-assembled standard versions available to save time

CE IP65 +50°C +122°F -30°C -22°F 95 dB 102 dB

808

- Full LED Flashing: Increase safety awareness and durable
- Versatile design: Enhance customers product image with professional look
- Dual mounting options (Base & Tube): Provide flexible mounting needs
- IP65: Ideal product for industrial applications

CE IP 65 +50°C +122°F -30°C -22°F PC PC/ABS 6 WS II

Multicolor Beacon 55

- Simple and elegant design, suitable for all types of modern machines
- Multicolor (three colors / seven colors), ease of installing and economical
- IP65 for all types of environmental applications
- Available with or without sounder, 85dB sound output

CE cULus IP65 +50°C +122°F -20°C -4°F 85 dB

Andon SmartBOX

- Rapid assistance reduces waiting times
- Reduces response times and prevents shutdowns
- Quick fault repair for more "units per hour"
- Intelligent reporting for lasting improvements
- Optimisation potential is made transparent

CE RoHS CLASSIFIED UL